



Worthington refillable steel cylinders for foam insulation and adhesive are manufactured in Jefferson, Ohio and Westerville, Ohio. They are engineered for repeat-use and rigorous job site demands



STANDARD SPECIFICATIONS

Model/Size	95 lbs	142 lbs	239 lbs	474 lbs	551 lbs	1000 lbs
Height (in)	29	33	49	46	50	56
Water Capacity (lb)	95	142	240	474	550	1,000
Nominal Tare Weight (lb)	28	52	77	145	205	270
Cylinder Diameter (in)	12	15	15	24	24	30
Cylinder Volume (cu. in)	2629.6	3930.56	6643.2	13120.32	15224	27680
Collar Diameter (in)	3	14	14	14	14	16
Collar Height (in)	4	8	8	7.6	7.6	7
Footring Diameter (in)	8	14	14	22	22	22
Standard Specification	DOT-4BA-240	DOT-4BW-240	DOT-4BW-240	DOT-4BW-240	DOT-4BW-240	DOT-4BW-240
Service Pressure (PSIG)	240	240	240	240	240	240
Test Pressure (PSIG)	480	480	480	480	480	480

All tare weights and dimensions are approximate.
Cylinders photos are not shown to scale.



**METRIC SPECIFICATIONS**

Model/Size	95 lbs	142 lbs	239 lbs	474 lbs	551 lbs	1000 lbs
Height (mm)	741	848	1250	1170	1270	1422
Water Capacity (L)	43	64	109	215	250	450
Nominal Tare Weight (kg)	13	24	35	66	93	123
Cylinder Diameter (mm)	305	373	373	610	610	762
Cylinder Volume (L)	43	64	109	215	250	450
Collar Diameter (mm)	79	356	356	356	356	406
Collar Height (mm)	100	213	219	193	193	176
Footring Diameter (mm)	198	351	351	559	559	559
Standard Specification	TC-4BAM-16	TC-4BWM-16	TC-4BWM-16	TC-4BWM-16	TC-4BWM-16	TC-4BWM-16
Service Pressure (BAR)	16	16	16	16	16	16
Test Pressure (BAR)	32	32	32	32	32	32

All tare weights and dimensions are approximate.
Cylinders photos are not shown to scale.

