

PROPYLENE

FUEL GAS



SPECIFICATIONS

STANDARD

MODEL/SIZE (LBS)	2	6	25.5*	60*	100*	420
HEIGHT (IN)	16.9	22.5	34.2	44.1	48	52
CAPACITY (GAL)	.95	1.5	6.0	14.2	23.6	99.1
WATER CAPACITY (LBS)	4.6	15	61	143	239	1,000
NOMINAL TARE WEIGHT (LBS)	5.5	8	25.9	48.1	74.8	298
CYLINDER DIAMETER (IN)	4	6.3	9	12	14.7	30
CYLINDER VOLUME (CU IN)	127	415	1,688	3,955	6,616	27,680
COLLAR DIAMETER (IN)	3	5.7	6.5	6.5	6.5	16
COLLAR HEIGHT (IN)	4.3	6.5	5.1	5.1	5.1	6.9
FOOTRING DIAMETER (IN)	4	6.3	7.8	12	14.5	22
VALVE	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
STANDARD SPECIFICATION	DOT-4BA260	DOT-4E260	DOT-4BW260	DOT-4BW260	DOT-4BW260	DOT-4BW260

METRIC

MODEL/SIZE (LBS)	2	6	25.5*	60*	100*	420
HEIGHT (MM)	429	571	868	1,120	1,219	1,321
CAPACITY (L)	1.7	5.4	22.1	52	86.7	360
WATER CAPACITY (KG)	2.1	6.8	27.6	65	108.4	450
NOMINAL TARE WEIGHT (KG)	2.5	3.6	11.7	21.8	33.9	135
CYLINDER DIAMETER (MM)	102	160	229	305	373	762
CYLINDER VOLUME (L)	2.1	6.8	27.6	65	108.4	450
COLLAR DIAMETER (MM)	76	144.8	165	165	165	406
COLLAR HEIGHT (MM)	109	165	130	130	130	175
FOOTRING DIAMETER (MM)	102	160	198	305	368	559
VALVE	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
STANDARD SPECIFICATION	DOT-4BA260	DOT-4E260	DOT-4BW260	DOT-4BW260	DOT-4BW260	DOT-4BW260

All dimensions are approximate.

*Also available with cap and flange without collar