

LPG STEEL PORTABLE CYLINDERS



STANDARD SPECIFICATIONS

MODEL/SIZE (LBS)	4.25	11	20	30	40	43.5	60*	100*
HEIGHT (IN)	11.8	16.6	17.2	23.7	29.3	32.5	44.1	48
LPG CAPACITY (GAL)	1	2.6	4.7	7.1	9.4	10.3	14.2	23.6
WATER CAPACITY (LBS)	12	26.2	47.6	71.5	95.2	103.6	143	239
NOMINAL TARE WEIGHT (LBS)	11	13.3	16.6	23.3	28.7	33.9	48.1	68
CYLINDER DIAMETER (IN)	9.1	9.1	12.3	12.3	12.3	12.3	12	14.7
CYLINDER VOLUME (CU. IN)	332	725	1,318	1,980	2,635	2,868	3,955	6,616
COLLAR DIAMETER (IN)	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
COLLAR HEIGHT (IN)	4	4	4	4	4	5.1	5.1	5.1
FOOTRING DIAMETER (IN)	9.1	7.8	7.8	7.8	7.8	12	12	14.5
HORIZONTAL DESIGN	-	-	Available	Available	Available	-	-	-
VALVE	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
STANDARD SPECIFICATION	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BW260	DOT-4BW240

METRIC SPECIFICATIONS

MODEL/SIZE (LBS)	4.25	11	20	30	40	43.5	60*	100*
HEIGHT (MM)	300	427	450	602	744	825.5	1,120	1,219
LPG CAPACITY (L)	3.8	9.8	17.3	26.9	35.6	39	53.8	86.7
WATER CAPACITY (KG)	5.4	11.9	21.6	32.4	42.2	47	65	108.4
NOMINAL TARE WEIGHT (KG)	5	6.0	7.5	10.5	13.0	15.4	21.8	30.8
CYLINDER DIAMETER (MM)	231	231	312	312	312	312	305	373
CYLINDER VOLUME (L)	5.4	11.9	21.6	32.4	42.2	47	65	108.4
COLLAR DIAMETER (MM)	165	165	165	165	165	165	165	165
COLLAR HEIGHT (MM)	102	102	102	102	102	130	130	130
FOOTRING DIAMETER (MM)	231	198	198	198	198	305	305	368
HORIZONTAL DESIGN	-	-	Available	Available	Available	-	-	-
VALVE	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
STANDARD SPECIFICATION	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BW260	DOT-4BW240

CONTACT US:

200 OLD WILSON BRIDGE ROAD
COLUMBUS, OHIO 43085
P: +1.614.438.3013

TOLL-FREE: 866.928.2657
CYLINDERS@WORTHINGTONINDUSTRIES.COM
WORTHINGTONINDUSTRIES.COM

MAKERS OF BETTER