

TAKE THE GUESSWORK OUT OF MONITORING UNDERGROUND TANK LEVELS.

With Otodata®'s state-of-the-art monitoring technology positioned to ensure the best signal, the Worthington Industries SmartLid monitor and mounting bracket is the reliable monitoring solution for underground tanks you've been looking for.



SMARTLID®

EASY TO INSTALL.

Every SmartLid monitor arrives pre-activated and the bracket can be secured to any underground riser with a single screw, making installation quick and easy.

EASY TO USE.

With a strong signal, long battery life and a convenient user-friendly app, you'll never be far from the accurate tank level information you need.

EASY TO SELL.

The SmartLid monitor bracket allows for one remote tank monitor solution for your entire fleet.



PEACE OF MIND COMES PRE-ACTIVATED.

Combining cutting-edge monitoring technology, Worthington Industries' legendary reliability, and improved compatibility, the SmartLid monitoring solutions are designed to make your job easier.

SAVE TIME AND MONEY.

- Longest battery life in the industry
- Dual SIM and LTE/Cat-M technologies for maximum coverage
- Automatic network updates for easier management
- Unlimited reports and alerts
- An app delivering real-time gas level data



SMARTLID MONITOR SPECS

	Standard	Metric
Dimensions	6.0 in x 6.3 in x 2.4 in	152.4 mm x 159.6 mm x 60.3 mm
Cellular Technology	Dual SIM, LTE, CAT-M	Dual SIM, LTE, CAT-M
Sensor & Gauge Input	Level	Level
Power Inputs	Hybrid LTC 7.2 VDC, LTC 3.6 VDC	Hybrid LTC 7.2 VDC, LTC 3.6 VDC
Battery life	~ 15 years	~ 15 years
Reporting Schedule	Unlimited, configurable	Unlimited, configurable
Operating Temperature Range	-22 F to 140 F	-40 C to 60 C

UNDERGROUND BRACKET

	Material	Standard	Metric
Underground Bracket Dimensions	316 Stainless Steel	6.1 in x 6.9 in x 0.9 in	154.9 mm x 175.3 mm x 22.9 mm