

Technical Specifications



Specifications	11 Lbs	17 Lbs	22 Lbs	31 Lbs V	31 Lbs FT
Propane Capacity (lbs)	11	16.8	22	31	31
Butane Capacity (lbs)	13.2	18.7	26	37	37
Tare weight (lbs)	8.6*	10.2*	12*	17.8*	18.7**
Gallon Capacity @60F	2.6	4	5.2	7.4	7.4
Water capacity (lbs)	27.5	40.4	53	75	75
Diameter (in)	12	12	12	12	12
Height (in)	15.1	18.3	22.5	28.3	28.3

*with OPD valve **with multivalve

Committed to quality, safety and innovation for composite cylinder technology

With more than 20 million units in use in close to 100 countries and an industry-leading safety record, our composite cylinders have become the standard for user-friendly LPG.

In North America Hexagon Ragasco products are offered under the Viking Cylinders® brand.

- Available in 4 standard sizes.
- Equipped with our standard OPD valve to provide simple and safe filling.
- 31 lbs cylinders can be equipped with a liquid draw valve for forklift operation.
- Viking Cylinders are approved for use and transport of LP Gas in the United States in accordance with DOT-SP 12706 and in Canada in accordance with TC SU 5931. They also comply with a wide range of international standards and approvals such as:
 - ISO 9001
 - ISO 11119-3
 - EN 14427
 - EN 12245
- Approved to be filled by any authorized LP-Gas filling location.
- Viking Cylinders are subjected to extensive testing including: cycle testing, extreme temperature testing, long term aging tests and static load fatigue tests.
- The cylinders require a 5 & 10 year recertification and have a 15 year life span.

In partnership with the industry



HEXAGON RAGASCO NORTH AMERICA INC.

1475 James Parkway Heath OH 43056 USA, 866-470-3737, info@vikingcylinders.com, www.vikingcylinders.com