



**STANDARD SPECIFICATIONS**

Model/Size (lbs)	6	10	20	30	40
Height (in)	22.5	15.9	20.2	25.9	32.1
LPG Capacity (gal)	1.4	2.4	4.7	7.1	9.4
Water Capacity (lbs)	15	23.8	47.6	71.5	95.2
Nominal Tare Weight (lbs)	8.1	9.7	13.0	16.5	19.5
Cylinder Diameter (in)	6.3	10.3	12.3	12.3	12.3
Cylinder Volume (cu. in)	415	664	1,318	1,999	2,635
Collar Diameter (in)	5.7	7.9	7.9	7.9	7.9
Collar Height (in)	6.5	5.5	5.5	5.5	5.5
Footring Diameter (in)	6.2	8	8	8	8
Horizontal Design	-	Available	Available	Available	Available
Valve	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD
Standard Specification	DOT-4E260	DOT-4E240	DOT-4E240	DOT-4E240	DOT-4E240

**METRIC SPECIFICATIONS**

Model/Size (lbs)	6	10	20	30	40
Height (in)	571	404	513	658	814
LPG Capacity (gal)	5.4	9.1	17.3	26.9	35.6
Water Capacity (lbs)	6.8	10.8	21.6	32.4	43.2
Nominal Tare Weight (lbs)	3.7	4.4	5.9	7.5	8.8
Cylinder Diameter (in)	160	261	312	312	312
Cylinder Volume (cu. in)	6.8	10.8	21.6	32.7	43.5
Collar Diameter (in)	144.8	200	200	200	200
Collar Height (in)	165	140	140	140	140
Footring Diameter (in)	158	203	203	203	203
Horizontal Design	-	Available	Available	Available	Available
Valve	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD
Standard Specification	DOT-4E260	DOT-4E240	DOT-4E240	DOT-4E240	DOT-4E240

All dimensions are approximate