



STANDARD SPECIFICATIONS

Model	7.5 in	9.5 in	12 in	
Height (in)	14.6	16.4	17.6	
Water Capacity (lb)	15.8	29.7	49.6	
Diameter (in)	7.5	9.5	12	
Cylinder Volume (cu. in)	438	822	1,378	
Standard Specification				
Service Pressure (PSIG)	260	260	260	
Test Pressure (PSIG)	325	325	325	
Standard Specification				
Service Pressure (PSIG)	400	320	400	320
Test Pressure (PSIG)	500	400	500	400

All dimensions are approximate.




FEATURES

- Rounded edges for safe handling
- Comfort grip for improved handling
- Arched design for light weight, enhanced durability and increased strength
- Wide 3.2" opening for easy valve access and filling
- Robust steel dip tube for consistent liquid delivery

STAMPS OF AUTHENTICITY

Guaranteed Quality. Guaranteed Worthington.



Shoulder



Collar



METRIC SPECIFICATIONS

Model	7.5 in	9.5 in	12 in	
Height (mm)	369.8	416.7	446	
Water Capacity (kg)	7.04	13.2	22.1	
Diameter (mm)	190.5	241.3	304.8	
Cylinder Volume (L)	7.2	13.5	22.5	
Standard Specification				
Service Pressure (BAR)	17.9	17.9	17.9	
Test Pressure (BAR)	23	23	23	
Standard Specification				
Service Pressure (BAR)	27.6	22	27.6	22
Test Pressure (BAR)	35	28	35	28

All dimensions are approximate.




FEATURES

- Rounded edges for safe handling
- Comfort grip for improved handling
- Arched design for light weight, enhanced durability and increased strength
- Wide 3.2" opening for easy valve access and filling
- Robust steel dip tube for consistent liquid delivery

STAMPS OF AUTHENTICITY

Guaranteed Quality. Guaranteed Worthington.



Shoulder



Collar