



STANDARD SPECIFICATIONS

Model/Size	30 lbs	123 lbs	1,000 lbs	
Height (in)	19.8	54.8	57.3	
Water Capacity (lb)	30	123	1,000	
Nominal Tare Weight (lb)	21	58	334	
Cylinder Diameter (in)	9.1	10	30	
Cylinder Volume (cu. in)	830	3,393	27,461	
Collar Diameter (in)	8	3.9	16	
Collar Height (in)	5.1	-	6.9	
Footring Diameter (in)	6.9	10	22	
Standard Specification	DOT-4BA-400	DOT-4BW-400	DOT-4BW-260	DOT-4BW-400
Service Pressure (PSIG)	400	400	260	400
Test Pressure (PSIG)	800	800	520	800

All tare weights and dimensions are approximate.
 Fore more information on 400 psig 1,000lb, DOT-4BW tare weight call Worthington Enterprises.
 Cylinders photos are not shown to scale.



METRIC SPECIFICATIONS

Model/Size	30 lbs	123 lbs	1,000 lbs	
Height (mm)	503	1,392	1,455	
Water Capacity (kg)	13.6	55.8	450	
Nominal Tare Weight (kg)	9.3	26.3	151.5	
Cylinder Diameter (mm)	231.1	254	762	
Cylinder Volume (L)	13.6	55.8	450	
Collar Diameter (mm)	203.2	98.4	406.4	
Collar Height (mm)	130	-	175	
Footring Diameter (mm)	175	254	558.8	
Standard Specification	DOT-4BA-400	DOT-4BW-400	DOT-4BW-260	DOT-4BW-400
Service Pressure (PSIG)	28	27	18	27
Test Pressure (PSIG)	55	54	36	54

All tare weights and dimensions are approximate.
 For more information on 400 psig 1,000lb, DOT-4BW tare weight call Worthington Enterprises.
 Cylinders photos are not shown to scale.