

INNOVATIVE TECHNOLOGY DESIGNED TO MAKE TANK MONITORING EASIER THAN EVER.

Featuring Otodata's state-of-the-art monitoring technology protected by a durable lid, SmartLid is the cutting-edge integrated lid and tank monitor solution that keeps service calls to an absolute minimum.



SMARTLID®

EASY TO INSTALL.

The lid arrives with the monitor pre-activated, making installation in the field quick and easy with no tools needed.

EASY TO USE.

With a strong signal, long battery life and a convenient user-friendly app, you'll never be far from the accurate tank level information you need.

EASY TO SELL.

SmartLid will transform your Worthington Industries vertical and horizontal tanks in ways that will boost sales and separate yourself from competition.



SMARTLID® MAKES TANK MONITORING EASIER AND MORE RELIABLE

Featuring Otodata®'s technology in our durable design, this integrated lid and tank monitor is easy to install and offers reliable monitoring that will keep your service calls to an absolute minimum.

SMARTLID®

EASY TO INSTALL.

The lid arrives with the monitor pre-activated, making installation in the field quick and easy with no tools needed.

EASY TO USE.

With a strong signal, long battery life and a convenient user-friendly app, you'll never be far from the accurate tank level information you need.

EASY TO SELL.

SmartLid will transform your Worthington Industries vertical and horizontal tanks in ways that will boost sales and separate yourself from competition.



LESS GUESSWORK. LESS SERVICE CALLS. LESS SERVICE CALLS.

The integrated lid and tank monitor created with you in mind.



FEATURES

- Waterproof polypropylene casing
- Long-lasting lithium thionyl chloride battery with super capacitor
- Monitor positioned to ensure strongest signal
- Fits the Worthington 420-pound heating tank with 16-inch collar

PUT A LID ON UNNECESSARY SERVICE TRIPS

- Longest battery life in the industry
- Dual SIM and LTE technology for maximum coverage
- Automatic network updates for easier management
- Unlimited reports and alerts
- An app delivering real-time gas level data



SMARTLID SPECS

	STANDARD		METRIC
Dimensions	15 in 16 in	18.82 in x 15.69 in x 5.48 in 19.7 in x 16.6 in x 5.4 in	478.03 mm x 389.53 mm x 139.20 mm 500.38 mm x 421.64 mm x 137.16 mm
Lid Weight	15 in 16 in	1.55 lbs 3 lbs	.70 kg 1.36 kg
Cellular Technology	Dual SIM, LTE, CAT-M		Dual SIM with CAT-M and NB-IoT
Sensor & Gauge Input	Level		Level
Power Inputs	Hybrid LTC 7.2 VDC, LTC 3.6 VDC		Hybrid LTC 7.2 VDC, LTC 3.6 VDC
Battery life	~ 15 years		~ 15 years
Reporting Schedule	Unlimited, configurable		Unlimited, configurable
Material	Polypropylene		Polypropylene
Operating Temperature Range	-22 F to 140 F		-40 C to 60 C

