



Worthington steel heating tanks are manufactured in Jefferson, Ohio. They are a reliable source of fuel for heat for both residential and commercial applications.



STANDARD SPECIFICATIONS

Model/Size (lbs of LPG)	100 lbs	200 lbs	420 lbs
Height (in)	49	40	52
LPG Capacity (gal)	23.8	47.6	100
Water Capacity (lb)	239	474	1,000
Nominal Tare Weight (lb)	68	142	271
Cylinder Diameter (in)	14.7	24	30
Cylinder Volume (cu. in)	6,616	13,120	27,720
Collar Diameter (in)	7.0	16	16
Collar Height (in)	4.3	5.0	5.0
Footring Diameter (in)	14.5	19	22
Valve	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
Standard Specification	DOT-4BW240	DOT-4BW240	DOT-4BW240

METRIC SPECIFICATIONS

Model/Size (lb. of LPG)	100 lbs	200 lbs	420 lbs
Height (mm)	1,245	1,016	1,321
LPG Capacity (L)	86.7	172	360
Water Capacity (kg)	108.4	215	450
Nominal Tare Weight (kg)	30.8	64.4	122.9
Cylinder Diameter (mm)	373	610	762
Cylinder Volume (L)	108.4	215	450
Collar Diameter (mm)	178	406	406
Collar Height (mm)	109	127	127
Footring Diameter (mm)	368	483	559
Valve	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
Standard Specification	DOT-4BW240	DOT-4BW240	DOT-4BW240

All dimensions are approximate.



Worthington steel system tanks are manufactured in Jefferson, Ohio. They are a reliable source of fuel for heat for both residential and commercial applications.



STANDARD SPECIFICATIONS

Model/Size (lbs of LPG)	100 lbs	100 lbs (Squat)	200 lbs	420 lbs
Height (in)	50	35	40	52
LPG Capacity (gal)	23.8	23.8	47.6	100
Water Capacity (lb)	239	239	474	1,000
Nominal Tare Weight (lb)	68	77	135	260
Cylinder Diameter (in)	14.5	18	24	30
Cylinder Volume (cu. in)	6,616	6,616	13,120	27,674
Collar Diameter (in)	11.4	16	16	16
Collar Height (in)	5.0	4.2	5.4	5.9
Footring Diameter (in)	14.5	16.6	19	22
Valve	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
Standard Specification	ASME	ASME	ASME	ASME

METRIC SPECIFICATIONS

Model/Size (lbs of LPG)	100 lbs	100 lbs (Squat)	200 lbs	420 lbs
Height (mm)	1,270	889	1,016	1,321
LPG Capacity (L)	86.7	86.7	172	360
Water Capacity (kg)	108.4	108.4	215	450
Nominal Tare Weight (kg)	31	35	61	118
Cylinder Diameter (mm)	368	457	610	762
Cylinder Volume (L)	108.4	108.4	215	450
Collar Diameter (mm)	290	406	406	406
Collar Height (mm)	127	107	137	150
Footring Diameter (mm)	368	422	483	559
Valve	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
Standard Specification	ASME	ASME	ASME	ASME

*MAWP = Maximum Allowable Working Pressure
All dimensions are approximate.